



Technical centre

Luxus Limited, Belvoir Way, Fairfield Industrial Estate, Louth, Lincolnshire, LN11 0LQ

Tel: + 44 (0) 1507 604941 • Fax: + 44 (0) 1507 609154 • info@luxus.co.uk • www.luxus.co.uk

Suitable for general injection mouldings requiring good visual appearance. Applications include lighting and consumer products.

Material:

Polycarbonate Black Compound

Type:

20003

Property

Specification

Units

Falling Dart Index	15 +	
Load at Peak <i>ISO/R 527</i>	2000	N
Stress At Peak <i>ISO/R 527</i>	49	N/mm ²
Extension <i>ISO/R 527</i>	6	%
Izod at Room Temperature <i>ISO 180: 1993</i>	16 +	KJ/m ²
Melt Flow Index <i>ISO 1133</i>	10 - 35	g/10 mins

Banned substance

A Reach , ELV, Pfos and banned substance compliance statement is available upon request. Where material is required for automotive applications, IMDS registration detail will be provided.

Packaging and COC/COA

Package options include 1000kg bulk bag or Octabox, 25Kg bag and bulk delivery. Luxus Type No grades are supplied under a certificate of conformance. A certificate of analysis can be provided upon request at an additional cost.

These are typical values for evaluation purposes and as a basis for evaluation and do not constitute any specific guarantee whatsoever.

Date

20/08/2007

Doc. No

DS20003/28